



# iMet-3200A

## 403MHz Commercial Antenna / Receiver

### Installation Options

Antenna	Roof or tower mount
Installation time	< 1/2 day

### 403MHz Antenna

Antenna type	Quadrifilar Helix
Construction	Aluminium / fibreglass composite
Polarization	Vertical, circular overhead
Max slant range	> 250 km*
Max altitude	> 35 km*

### Receiver

Type	Superheterodyne
Freq control	Synthesized with AFC
Bandwidth	15kHz
Modulation	FM, FSK
Sensitivity	-118 dBm

### Computer Requirements

Type	Any current PC
Operating system	Windows
Connection	USB

### Key Features

- Designed for synoptic soundings
- Overhead and long-range antenna coverage
- Integrated GNSS providing accurate station location
- Combined antenna/receiver with single data cable interface
- All-weather operations, includes built-in heaters
- Compatible with D-Met sounding software
- Compatible with all 403MHz InterMet radiosondes

### System Overview

Compatibility	All InterMet 403 MHz GPS radiosondes
Frequency	400.15 - 406 MHz
Operating mode	Fixed installation
Operating Environment	All weather
System architecture	Digital
MTBF	> 2400 hours
Useful life	10 years
Sounding Software	D-Met

### Operating Parameters

Power	100-240 VAC, 50 / 60 Hz
Temperature	-40 to +55 °C
Antenna weight	4 kg
Antenna length	1.3 m

*This is an integrated antenna and receiver which simplifies installation and usage for fixed stations. The antenna design has been tailored to cover overhead as well as long-range operations. This antenna is ideal for users that are involved in regular synoptic observations*



33 Estmil Road, Diep River, 7800,  
Cape Town, South Africa  
Phone: +2721 715 1120  
email: [info@intermetafrica.com](mailto:info@intermetafrica.com)  
[www.intermetafrica.com](http://www.intermetafrica.com)

*Specifications subject to change without notice  
\* Subject to balloon dimensions and atmospheric conditions*